

High Quality Duplex Fiber Patch Cord, MM OM4, LC - SC



DESCRIPTION

All LIGHTWIN[®] fiberoptic patchcords are processed to a high-quality product with certain ferrules and processing methods. These cables are suitable for all fiberoptic applications in a wide range of telecommunications applications. Typical application areas are patches in data centers, server or network cabinets, as well as FTTH (Fiber to the Home). The use of singlemode ferrules for the LIGHTWIN[®] multimode patch cables and specially selected ferrules with the lowest tolerances for the LIGHTWIN[®] singlemode patchcables achieves damping values that go far beyond the required standards according to ISO / IEC. Other advantages of the LIGHTWIN[®] fiberoptic patchcable:

- LIGHTWIN[®] Lifetime Warranty
- 100% tested, with individual measurement protocol for return loss and insertion loss
- Use of bend insensitive fibers. Therefore no increase of the damping at a narrow bending radius
- Aramide yarn reinforced strain relief, halogen- free and flame- retardant coating according to IEC-60754-2, IEC-60332-1 and IEC-61034
- All plug combinations and lengths on request at short notice

FEATURES

- Multimode 50/125µm OM4 bend insensitive fiber
- 2,8mm cable diameter (Figure 8)
- Special selected ferrule
- Serial number for every cable
- LSZH flame retardant coating
- Measurement protocol for RL & IL
- Lightwin[®] Lifetime Warranty
- Other lengths and customized labeling on request available!

High Quality Duplex Fiber Patch Cord, MM OM4, LC - SC

PRODUCT FEATURES

Cable Length	1.0 m / 1.5 m / 10.0 m / 15.0 m / 2.0 m / 20.0 m / 3.0 m / 4.0 m / 5.0 m / 7.5 m
Cable Diameter	2,8 mm
Fiber Type	50/125µm
Fiber Cable Variation	Duplex
Fiber Category	Multimode OM4
Fiber Connector 1	LC
Fiber Connector 2	SC
Coating	LSZH
Certificate	Measurement Report for RL & IL

APPLICATION

General information about fiberoptic cables: Identical designations for fiberoptic patchcables may include: jumper cable, adapter cable, connection cable, jumper. Fiber optic cables operate with light, so they do not (or cause) susceptibility to electromagnetic interference, such as comparatively copper wires. Because of the low attenuation of the optical cables, it is also possible to bridge distances of more than 100 km without optical amplification.

PRODUCT NUMBER		EAN Code
LDP-50 LC-SC 1.0 OM4	1.0 Meter	9120046984674
LDP-50 LC-SC 1.5 OM4	1.5 Meter	9120072481345
LDP-50 LC-SC 10.0 OM4	10.0 Meter	9120046984711
LDP-50 LC-SC 15.0 OM4	15.0 Meter	9120046984728
LDP-50 LC-SC 2.0 OM4	2.0 Meter	9120046984681
LDP-50 LC-SC 20.0 OM4	20.0 Meter	9120046984735
LDP-50 LC-SC 3.0 OM4	3.0 Meter	9120046984698
LDP-50 LC-SC 4.0 OM4	4.0 Meter	9120046985640
LDP-50 LC-SC 5.0 OM4	5.0 Meter	9120046984704
LDP-50 LC-SC 7.5 OM4	7.5 Meter	9120046980485