

---

CAT5E Patch Cordbox Outdoor, schwarz, F/UTP

---



#### FEATURES

- Category 5e patchcable
- Stranded cable for patchcord assembling
- Shield: F/UTP shielded
- 4-pairs twisted
- Wires: AWG27
- Compliant with ISO/IEC 11801 Ed.2 EIA/TIA 568 B.2 and EN 50173
- Coating: UV resistant, LSZH
- Color: black
- Appearance: 100m or 305m box

## CAT5E Patch Cordbox Outdoor, schwarz, F/UTP

### PRODUCT FEATURES

Outer Diameter	5.2 mm
Operating Conditions	-10°C - +60°C
Bending Radius	4x OD (Perm.), 8x OD (Installtion)
Individual Shield	none
Color	Black
Overall Shield	Foil
DC Resistance	max. 93.8 Ohm/km
Installation Temperature	0°C - +50°C
Isolation	HDPE, Diameter 0.9 mm (nom.)
Cable Length	100 m / 305 m / Yard Good
Cable Structure	8 conductors, twisted in 4 pairs
Type of Cable	4x2xAWG26/7
Capacity	max. 56 pF/m
Category	CAT5E
Storage Temperature	-20°C - +60°C
Coating	UV resisdant PE, LSZH
Velocity of Propagation NVP	0.69 c (nom.)
RoHS Compliance:	EU Directive 2002/95/EC
Shield	F/UTP shielded
SKEW	max. 45 ns/100m (1-100 MHz)
Standards & Protocols	ISO/IEC 11801 (2002), EN 50173 (2002), EN 50288-3-1 (2nd Ed.), IEC 60332-1
Characteristic Impedance	100 ± 15 Ohm (1-125 MHz)
Tension	90 N

### APPLICATION

- Cable for horizontal (primary)and vertical (secondary) cabling
- Installationcable for indoor use in structured cabling systems.
- Suitable for all applicati ons Class D like:
  - ISDN
  - Ethernet 10 BaseT
  - Fast Ethernet 100 BaseTX
  - Gigabit Ethernet 1000 BaseT
  - Token Ring 4/16 Mbit/s
  - ATM 155 Mbit/s
  - VoIP (Voice over IP)
  - PoE (Power over Ethernet)

Notice !! Cutting costs and, depending on the length, drum costs are incurred for goods sold by the meter.

PRODUCT NUMBER		EAN Code
VKBOX OUTDOOR 100.0	100 Meter	9120046983851
VKBOX OUTDOOR 305.0	305 Meter	9120046985299
VKBOX OUTDOOR MW	Yard Good	