


DS-SBOX-03 Hikvision Outdoor Surveillance Box



- High strength Polymer Material(Flame Proof UL94-V0)
- IP66 & IK10 Protection
- Fast Deployment & Easy Installation to be mounted in a pole or a wall
- Highly adaptable with Hikvision IPC, PTZ and IP Horn Speakers

▪ Specification

General	
Material	PC/ASA; Hikvision White(RAL 9003)
Dimension	448.72mm x 387.53mm x 225.44mm
Weight	5.2kg
Startup and Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F). Humidity 95% or less (non-condensing)
General Function	Loading Capacity of Front Panel is 8kg; side panel is 5kg
Packing List	Security Box x1 Installation back Plate x1 Pegboard x1 Shelf board x1 Din Rail x1 Phillips head Screw M8x20 x4 Phillips head Screw M8x12 x2 Phillips head Screw M4x10 x12 Self-tapping Screw M3x10 x10 Hex Head Phillips Screw M8x25 x4 Hex socket Screw M6x25 x4 Hexagon Socket Screwdriver x1 Cylindrical pin M4x40 x4 Waterproof Cable connector 1(5-6.5mm) x3 Waterproof Cable connector 2(6.5-8mm) x3 Network cable piercing accessories x1 Cable Gland G3/4 x1 Cable Gland M20 x2 Metal strapping band(80-200mm) x5
Approval	
Protection	IP66, IK10


▪ Available Model

DS-SBOX-03


Dimension


Unit: mm (inch)

Box Dimension:



Front Panel:





▪ Accessory

With Cameras:



DS-1618ZJ



DS-1602ZJ



DS-4603ZJ-WA



DS-1280ZJ-XS



DS-1280ZJ-DM21



DS-1260ZJ



DS-1280ZJ-DM46



DS-1280ZJ-DM45



DS-1280ZJ-DM8




DS-1280ZJ-PT6

Box Installation:



Metal strapping band ((x5 included)
(Pole Mount 80-200mm)



Installation Plate (included)
(Wall Mount, M8 bolts need to purchase)

Recommended Compatible List:

Compatible Junction	Recommended Models	Compatible Junction	Recommended Models
DS-1280ZJ-XS	Fixed Bullet: ● DS-2CD20x3G2 ● DS-2CD30x3G2 ● DS-2CD20x7G3 ● DS-2CD30x7G3	DS-1618ZJ (Front Panel Only)	4 inch PTZ: ● DS-2DE4xxxx ● DS-2SE4xxxx
DS-1280ZJ-DM8	Fixed Turret: ● DS-2CD23x3G2 ● DS-2CD33x3G2	DS-4603ZJ-WA (Front Panel Only)	7 inch PTZ: ● DS-2DF7Axxxx
DS-1280ZJ-PT6	Fixed Turret: ● DS-2CD23x7G3 ● DS-2CD33x7G3	No need to order additional accessories	Bullet: ● DS-2CD3Ax6G2T ● DS-2CD36x7G3T ● iDS-2CD7Ax6G2 ● iDS-2CD7Ax5G2 ● iDS-2CD8Ax6G2 ● DS-2XC3Tx6G0H ● DS-2XC36x6G0H Dome: ● DS-2CD27x7G2H(PTRZ) ● DS-2CD37x6G2H(PTRZ) ● iDS-2CD75x6G2 ● DS-2XC31x6G0H Thermal Bullet: ● DS-2TD2628 Speaker: ● DS-QAZ1307G1-E
DS-1260ZJ	VF Bullet: ● DS-2CD26x3G2 ● DS-2CD36x3G2 Fixed Bullet: ● DS-2CD2Tx3G2 ● DS-2CD3Tx3G2		
DS-1280ZJ-DM45	VF Dome: ● DS-2CD27x7G3T ● DS-2XC37x7G3T ● iDS-2CD7146G2		
DS-1280ZJ-DM46	Fixed Dome: ● DS-2CD21x3G2 ● DS-2CD31x3G2 ● DS-2CD21x7G3 ● DS-2CD31x7G3 VF Dome: ● DS-2CD27x3G2 ● DS-2CD37x3G2		
DS-1280ZJ-DM21	Thermal Turret: ● DS-2TD1228		

*This table is just taking part of Hikvision compatible models for your reference, for other models that are not in the list please check the holes

See Far, Go Further



www.hikvision.com
support@hikvision.com

