

IP68 Outdoor hood sleeve, compact design, max. number of fibres 144



DESCRIPTION

- High quality thermoplastic material - watertight
- BASE and DOME (IP68, IEC 529) with clamp and O-ring closing system
- Management of various types and diameters of tube cables, slotted core
- Equipped with a clamp system to seal the BASE to the DOME
- Dedicated area to midspan cable modules (loop cable)
- Internal STACK can be configurable with SAMX HD modules according to the splice capacity needs
- BASE is suitable for both the heat-shrinking sealing kit and cold sealing kit (BASE A and BASE C)

Installation:

- Handholes, manholes and chambers
- Poles
- Pot-head

FEATURES

- 144 Fibers
- Height: 380 mm
- Max. numbers of modules: 6
- Cable entry for uncutted cables:
 - 1 oval cable entry
 - 6 round cable entries
- Watertight IP68 (IEC 529)
- Suitable for traditional cables and micro-cables with G652 to G657 fibers
- Inside a STACK is used to fix SAMX splicing modules on both sides. The internal STACK space can be used as storage for the midspan looped loose tubes.
- All closures are equipped with a re-entable locking system made up of a CLAMP and a specific O-ring which guarantees the seal.
- All Optotec's closures have an RFID system and QR code to access installation instructions.

IP68 Outdoor hood sleeve, compact design, max. number of fibres 144

PRODUCT FEATURES

Dimensions	290 x 380 x 150 mm
Number of Modules	4
Cable Entry	1x oval (88 x 41 mm), 6x round (Ø 32 mm)
Material	Aluminium, plastics
max. Number of Splices	max. 288
Safety Class	IP68
EAN Code	9120072488139
Weight	2 kg
PRODUCT NUMBER	LFC2 COMPACT 1/6-380

APPLICATION

- Butt-end closures for trunk, branch and pot-head joints
- Underground and overhead
- Underground networks: inside handholes/manholes

- Aerial networks: on pole