

OMB-24-050 RTNC
2,4 GHz 5dBi Indoor Omni

OMB-24-050 RTNC
2,4 GHz 5dBi Indoor Omni

Features

This compact 2.4GHz omnidirectional „rubber-duck“ WiFi antenna provides broad coverage and 5dBi gain. It is a coaxial sleeve design with an omni-directional pattern.

It is ideally suited for IEEE 802.11b and 802.11g wireless LANs, This flexible antenna features a tilt-and-swivel reverse-polarity SMA connector, allowing them to be used vertically, at a right angle, or any angle in-between. It is suitable as a replacement RF antenna for many access points and radios that are equipped with reverse-polarity SMA connectors including D-LinkR, LinksysR WET11 and others. Also can use with our Mage base

- 802.11b, 802.11g
- RP-TNC(M) Connector
- Flexible WiFi antennailt and swivel design

Frequenzbereich	2400-2500 MHz
Verstärkung	5 dBi
3dB Abstrahlung V/H	360°
Abmessungen: LxBxH	200 mm Length
Anschluss	RP-TNC Male
Inkludiertes Befestigungsset	-

Frequency	2400-2500 MHz
Gain	5 dBi
3dB Beamwidth V/H	360°
Dimensions: LxWxH	200 mm Length
Connector	RP-TNC Male
Included mounting kit	-

Artikelnummer / Part number

OMB-24-050 RTNC

