



| | | |
|---------------|-------|---------|
| ITEM NO. | COLOR | RAL |
| DVP-TRIO-K6 8 | GREY | RAL7035 |
| | BLACK | RAL9005 |

MATERIAL LIST:

| ⑦ | Upper Panel Cover: | 1.0mm thickness Metallic Panel (SECC) | 1 | |
|-----|--------------------|---|-------|--------|
| ⑥ | Bottom Panel : | 1.5mm thickness Metallic Panel (SECC) | 1 | |
| ⑤ | RJ45 Jack : | Housing-Fireproof PBT UL-94V0 Pin-8P8C 3u" gold plated | 8 | |
| ④ | PCB | FR-4 1.6mm UL 94V0 | 1 | |
| ③ | IDC BODY | Fireproof PC/ABS UL-94V0/With Colour Coded Printing T568A/B | 8 | |
| ② | IDC PIN | Phosphor Bronze & Tinned | 64 | |
| ① | IDC TERMINAL | For 22-26 AWG Cable | 8 | |
| NO. | PARTS NAME | SPECIFICATION STANDARD | QT' Y | REMARK |

NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125V AC RMS
- 2. CURRENT RATING : 1.5A mp
- 3. CONTACT RESISTANCE : 100 MILLI OHMS MAX
- 4. INSULATION RESISTANCE : 1000M OHMS MIN @ 500V DC
- 5. DIELECTRIC STRENGTH : 750V AC RMS 60Hz, 1MIN
- 6. CAT. 6 PERMANENT LINK : CONFORM TO ANSI/TIA/EIA-568 B. 2-1

ENVIRONMENTAL:

- 1. STORAGE : -40° TO+85°
 - 2. OPERATION : 0° TO+70°
- RJ45 JACK COMPLY TO REQUIREMENTS OF IEC-60603-7-5
MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68

MECHANICAL

- 1. RJ45 JACK LIFE: 750 TIMES MIN
- 2. IDN LIFE : 200 TIMES MIN

Accessory:

- 1. M3 Screw Set, For Pre-Assembled Ground Wire
 - 2. Cable Tie (75X1.9mm) X 8Pcs
 - 3. Instruction Sheet
 - 4. expanded screw X 2 Set
- PACKING: 1pcs /PE BAG + INNER CARTON
COLOUR: GRAY RAL 7035

RoHS COMPLAINT



| | | | | | | | | | | | |
|--|--|------|--|--------------|--|----------|--|---------------|--|------|--|
| | | | | | | ITEM NO. | | DVP-TRIO-K6 8 | | | |
| | | A1 | | PRODUCT NAME | | | | UNIT | | MM | |
| | | A | | DRAWNBY | | CHECKBY | | APPOBY | | DATE | |
| | | DATE | | REV. | | | | | | | |