

QuPSU P248E

P/N: P248E

Passive PoE Power Supply EU

PoE power supply dedicated to all QuSpot, QuMax and QuMini antennas with installed all Teltonika routers inside.

- Passive PoE Power Supply EU
- Output: 24V, 0.8A
- Input: AC100-240V 50/60Hz
- EU power cord
- Wall mount holder included
- CE, ATE, HIPOT
- Caution: Indoor use only



VERSION 1.01

OUTDOOR

Use LTE router wherever you want

ANTENNA

Maximize your signal with QuWireless antennas

SOLUTION

Plug LTE router and you are good to go

ELECTRICAL INPUT SPECIFICATION

Input voltage	110 ... 240VAC
Input frequency	50 ... 60Hz
Input current	max. 2A RMS
Inrush current	max. 30A
AC leakage current	max. 3.5mA
Efficiency	min. 80% @ 100VAC, 84% @ 240VAC
Dielectric strength (primary to secondary)	2kVAC/5mA/1s
Input socket	IEC320-C6
AC power cord	0.75m length, 3 pins EU plug

ELECTRICAL OUTPUT SPECIFICATION

Output voltage	24VDC
Min. load	0A
Max. load	0.8A
Peak load	1.32A
Output power	19.2W
Line regulation	± 3%
Load regulation	± 5%
Ripple	240mVpp
Turn on delay time	max. 5s
Rise time	max. 40ms
Hold up time	min. 5ms
Overshoot	max. 15%
Protections	Short circuit, over current (110 ... 200% of DC output)
Ethernet ports	Input (LAN): 1x RJ45 10/100Mbps Output (PoE): 1x RJ45 10/100Mbps
PoE mode	mode B: pins 4,5 + / pins 7,8 -
LEDs	Green: Power supply is on, Blue: PoE device connected

OTHER

MTBF	30,000 operating hours confidence-level at 80% load, 25°C
Operating temperature	-10°C ... +45°C
Storage temperature	-20°C ... +85°C
Humidity	5% @ 0°C, 90% @ 40°C
Size	84 x 44 x 30mm (LxWxH)
Safety	CE: EMC/LVD / FCC Part 15 Class B/ EN55022 Class B/ EN55024



HEADQUARTER:

Wireless Instruments sp. z o.o.

ul. Kościuszki 27

52-116 Iwiny

POLAND

sales@quwireless.com

tel 1. +48 601 366 369

tel 2. +48 577 667 761

www.quwireless.com