



04	HEAT SHRINK TUBE (NO GLUED)	BLACK
03	N Plug CONNECTOR	NICKEL N-M C 200
02	COAXIAL CABLE	BLACK HDF 200
01	N Plug CONNECTOR	NICKEL N-M C 200
NO.	DESCRIPTION	FINISH ITEM

THIS DOCUMENT IS THE PROPRIETARY PROPERTY OF CONNEKT PRECISION ELECTRONICS CO., LTD	DRAWN	Justice	SCALE	2 : 1
	DESIGNED	Justice	UNIT	mm
	APPROVED	Y. Q. T	DATE	JUL/18/2019
ROHS COMPLIANT				
GENERAL TOLERANCES		0.5~10.0mm ±0.2 11~100mm ±5.0 101~500mm ±10.0 501~1000mm ±15.0 1001~2000mm ±20.0 UNLESS OTHERWISE SPECIFIED		
TITLE: 200 N-N MM x.x				
DESCRIPTION: Double shielded "Low Loss" cable with assembled assembled RF connectors.				
<i>This HDF 200 cable family of "low loss cables" differs among other things by double shielding and lower attenuation or cable capacity from the standard cables (e.g. RG58). HDF 200 is a low attenuation, double shielded 50 Ohm coaxial cable that is approved up to 6GHz and can be used up to 10GHz. Due to the dielectric, the solid, yet soft inner conductor of solid copper is 1.12mm in diameter, very large in relation to the outer diameter of 4.95mm. Fields of application: Medical, maximum frequency up to 6 GHz, antennas, military applications, EMC, etc. HDF 200: sheath color: black, 50 Ohm, double shielded, temperature range from -40 / +85°C.</i>				