

CAT6A Flush Outlet, shielded, RAL9010, LSA Connector


DESCRIPTION

CAT6A shielded outlet with LSA socket. This outlet allows data transmission for up to 10 Gigabit Ethernet. The front panel is design compatible and has 2 dust-protected, shielded RJ45 ports. The cables can be connected from the left and right. ISO / IEC 11801, EN 50173-1 Class E - Sub A up to 500MHz, Suitable for Power-over-Ethernet applications, Service life:> 750 mating cycles

FEATURES

- Outlets with LSA+
- CAT. 6A according to ISO / IEC 11801 or EN50173
- Size: 80 x 80 x 381 mm
- Color: white, RAL9010
- Suitable for 10 Gbit Ethernet
- Integrated strain relief for installation cables
- 2 x shielded RJ45 sockets
- Duct system, surface / built-in installation possible
- Material: die-cast zinc, cover: plastic

- Integrated labeling field
- Design compatible

CAT6A Flush Outlet, shielded, RAL9010, LSA Connector

PRODUCT FEATURES

Connectors	2
Pining	TIA/EIA 568 A/B
Color	White
Category	CAT6A
Material	Metal
Shield	shielded
EAN Code	9120072488344
Weight	0.23 kg
PRODUCT NUMBER	DD-WW-K6A UP2 WS