



Note:
RoHS 2.0 & Reach Compliant

Test Grade Designation:Each to Reference		
Grade IL/RL	Standard	
Insertion Loss (IL)	≤0.2dB	IEC 61300-3-4
Return Loss(RL)	≥30dB	IEC 61300-3-6
Test Wavelength	850nm	
End face inspection	×400	

ITEM NO.	Length
LDP-50 LSH-LSH 1.0 OM4	1m
LDP-50 LSH-LSH 2.0 OM4	2m
LDP-50 LSH-LSH 5.0 OM4	5m

Packing:1pc/PE Bag+Lightwin Label

MATERIAL LIST:

⑦	LSH 3.0 BOOT Red	2pcs	
⑥	Fiber Optical Cable Erika Violet(RAL4003) OM4 50/125um Duplex Ø2.0*6.0mm LSZH	L	
⑤	Black Heat Shrink Tube	2pcs	
④	Ring 1, 2	4pcs	
③	LSH 3.0 Black BOOT	2pcs	
②	LSH Erika Violet(RAL4003) UPC Connector	4pcs	
①	LSH Metal Dust Cap	4pcs	

NO.	SPECIFICATION STANDARD	QT' Y	REMARK
BY	CHK	REVISION RECORD MODIFICATIONS	DATE

Lightwin®
European Fibre Optic Solutions

CUSTOMER	ITEM NO.	See the chart
PRODUCT NAME	LSH(E2000)/UPC-LSH(E2000)/UPC Duplex OM4 Patch Cord 3.0	UNIT MM
DRAWNBY	CHECKBY	APPOBY
TT	LF	DATE
		2021-06-08

2021-06-08 A REV.