



Note:
RoHS 2.0 & Reach Compliant

| | | |
|--|----------|---------------|
| Test Grade Designation:Each to Reference | | |
| Grade IL/RL | Standard | |
| Insertion Loss (IL) | ≤0.2dB | IEC 61300-3-4 |
| Return Loss(RL) | ≥50dB | IEC 61300-3-6 |
| Test Wavelength | 1310nm | |
| End face inspection | ×400 | |

MATERIAL LIST:

| | | | |
|-----|---|-------|--------|
| ⑦ | LC 3.0 BOOT White | 1 pc | |
| ⑥ | LC UPC Connector Blue | 1 pc | |
| ⑤ | LC Dust Cap White | 1 pc | |
| ④ | Fiber Optical Cable Yellow G652.D OS2 9/125um Simplex $\phi 3.0 \pm 0.2$ LSZH | L | |
| ③ | LSH 3.0 Boot Blue | 1 pc | |
| ② | LSH UPC Connector Blue | 1 pc | |
| ① | LSH Metal Dust Cap | 1 pc | |
| NO. | SPECIFICATION STANDARD | QT' Y | REMARK |

| ITEM NO. | Length |
|--------------------|--------|
| LSP-09 LSH-LC 1.0 | 1m |
| LSP-09 LSH-LC 10.0 | 10m |
| LSP-09 LSH-LC 2.0 | 2m |
| LSP-09 LSH-LC 3.0 | 3m |
| LSP-09 LSH-LC 5.0 | 5m |

Packing:1pc/PE Bag+Lightwin Label



| | | | | | |
|----|-----|-------------------------------|------|------|--|
| | | | | | |
| BY | CHK | REVISION RECORD MODIFICATIONS | DATE | REV. | |

| | | | | | |
|--------------|---|----------|---------------|----|--|
| CUSTOMER | | ITEM NO. | See the chart | | |
| PRODUCT NAME | LSH(E2000)/UPC-LC/UPC Simplex OS2 Patch Cord Yellow 3.0 | | UNIT | MM | |
| DRAWNBY | CHECKBY | APPOBY | DATE | | |
| TT | LF | | 2021-06-08 | | |