



Note:  
RoHS 2.0 & Reach Compliant

Test Grade Designation: Each to Reference		
Grade IL/RL	Standard	
Insertion Loss (IL)	≤0.2dB	IEC 61300-3-4
Return Loss (RL)	≥30dB	IEC 61300-3-6
Test Wavelength	850nm	
End face inspection	×400	

**MATERIAL LIST:**

⑫	SC Clip Erika Viollet (RAL4003)	1pcs	
⑪	SC 3.0 BOOT Red	1pcs	
⑩	LSH 3.0 BOOT Red	1pcs	
⑨	SC Dust Cap Transparent	2pcs	
⑧	SC Erika Viollet (RAL4003) Connector	2pcs	
⑦	SC 3.0 Black BOOT	1pcs	
⑥	Fiber Optical Cable Erika Viollet (RAL4003) OM4 50/125um Duplex OS2 G652.D φ3.0*6.0mm LSZH	L	
⑤	Black Heat Shrink Tube	2pcs	
④	Ring 1, 2	4pcs	
③	LSH 3.0 Black BOOT	1pcs	
②	LSH Erika Viollet (RAL4003) Connector	2pcs	
①	LSH Metal Dust Cap	2pcs	

PACKING: 1pc/PE Bag+Lightwin Label

ITEM NO.	Length
LDP-50 LSH-SC 1.0 OM4	1m
LDP-50 LSH-SC 10.0 OM4	10m
LDP-50 LSH-SC 2.0 OM4	2m
LDP-50 LSH-SC 3.0 OM4	3m
LDP-50 LSH-SC 5.0 OM4	5m



NO.	SPECIFICATION STANDARD	QT' Y	REMARK
BY	CHK	REVISION RECORD MODIFICATIONS	DATE
		NEW	2021-06-08
			A
			REV.

CUSTOMER		ITEM NO.	See the chart
PRODUCT NAME	LSH/UPC-SC/UPC Duplex OM4 Patch Cord 3.0	UNIT	MM
DRAWN BY	CHECK BY	APPO BY	DATE
TT	LF		2021-06-08