



Note:
RoHS 2.0 & Reach Compliant

Test Grade Designation:Each to Reference	
Grade IL/RL	Standard
Insertion Loss (IL)	≤0.2dB IEC 61300-3-4
Return Loss (RL)	≥60dB IEC 61300-3-6
Test Wavelength	1310nm
End face inspection	×400

MATERIAL LIST:

⑦	SC 3.0 B00T Green	1 pc	
⑥	SC APC Connector Green	1 pc	
⑤	SC Dust Cap Transparent	1 pc	
④	Fiber Optical Cable Yellow G652.D OS2 9/125um Simplex $\phi 3.0 \pm 0.2$ LSZH	L	
③	LSH 3.0 Boot Green	1 pc	
②	LSH APC Connector Green	1 pc	
①	LSH Metal Dust Cap	1 pc	
NO.	SPECIFICATION STANDARD	QT' Y	REMARK

ITEM NO.	Length
LSP-09 LSHAPC-SC/APC 1.0	1m
LSP-09 LSHAPC-SC/APC 10.0	10m
LSP-09 LSHAPC-SC/APC 2.0	2m
LSP-09 LSHAPC-SC/APC 3.0	3m
LSP-09 LSHAPC-SC/APC 5.0	5m

Packing:1pc/PE Bag+Lightwin Label



BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		NEW	2021-06-08	A

CUSTOMER		ITEM NO.	See the chart	
PRODUCT NAME	LSH(E2000)/APC-SC/APC Simplex OS2 Patch Cord Yellow 3.0	UNIT	MM	
DRAWNBY	CHECKBY	APPOBY	DATE	
TT	LF		2021-06-08	