

## FTTH OTO Box, 4-fibers, 4x LC/APC Couplings, Breakoutcable 30 - 100m, G.657A2

**DESCRIPTION**

The pre-assembled OTO box contains 2 fibers (SC Duplex) with adapters and can be obtained with 30, 50 or 100m in-house cable. By using the particularly bend-insensitive A2 singlemode fiber, the cable can be almost kinked without being damaged. Installation is impressively simple: In addition to simple wall mounting, the OTO Box can be mounted horizontally or vertically on a top-hat rail.

Alternatively, the OTO Box can be attached to a flush-mounted box without opening it. For this purpose there are 2 holes at a distance of 6.4 cm below the labeling field. The OTO box is delivered already rolled up in a cardboard box. The OTO Box from Lightwin® meets the highest security standards to ensure the best security, especially in private households.

**FEATURES**

- FTTH OTO Box Optical Termination Outlet)
- Colour: White
- 4x LC/APC Couplings
- Fiber: Singlemode, bend insensitive G.657A2 Fiber
- Fire protection class Eca
- Wallmounting, suitable for empty box or DIN rail
- Length: 30m / 50m / 100 m

FTTH OTO Box, 4-fibers, 4x LC/APC Couplings, Breakoutcable 30 - 100m, G.657A2

**PRODUCT FEATURES**

Color	White
Number of Fibers	4
Flame Rating	
Cable variant	Round
Cable Length	100 m / 30.0 m / 50.0 m
Cable Diameter	2.2 mm
Fiber Type	9/125µm, OS2, G.657.A2
Fiber Connector	4x LC/APC Coupling
Coating	LSZH
Rodent Protection	no
Product Family	OTO Boxes
Certificate	RoHS 2011/65/EU&(EU )2015/863

PRODUCT NUMBER		EAN Code
WALL OUTLET 4XLC/APC 100	100 m	
WALL OUTLET 4XLC/APC 30	30 m	9120117651894
WALL OUTLET 4XLC/APC 50	50 m	