


SLIM-L-UU-K6A ORANGE

CAT6A 10 Gigabit LightPatch Cord round, U/UTP, Ø 3,6 mm, orange

Features

- Category 6A Patchcord
- For 10 Gigabit Datatransfer use
- Tested with Fluke Cable-Certifier in Channel Test
- Shield: U/UTP unshielded
- Colour: Orange, similar RAL2004
- Special RJ45 plug with break-proof jack
- 4-pairs twisted
- Wires: AWG28 100% copper
- Coating: LSOH - flame retardant
- 11 different length
- Innovative boot design



Application

- Overcrowded server or network cabinets or cable channels
- Switches with high port densities: with very short cables, it is easy to patch from switch to switch or switch to panel without a cable management panel
- Connection of terminal devices at the table (VoIP phones, Printer, PC, Notebook), as the cables are extremely flexible and therefore easy to lay on a desk
- Industrial applications where Ethernet connectivity is required but space is limited
- As a patch cord in the Notebook bag for Technicians and Field Staff
- In a private environment, to lay a patch cord under the carpet, the chair rail or even through a window seal

Description

The new KAT6A LIGHT patch cables from SLIM® set new standards in network technology. Thanks to their extremely flexible and thin design, these slim cables now make patching easier for 10 Gigabit applications too.

The LIGHT patch cables are round, twisted in pairs, and unshielded. They meet the requirements for transmitting 10/100/1000 Mbit and even 10 Gigabit.

Another major advantage of LIGHT patch cables is their flame-retardant outer jacket material. In addition, the special RJ45 connector is made of a break-resistant material that prevents the latch from breaking off. The latch can be bent back and forth hundreds of times without breaking.


Power over Ethernet (PoE) is also supported in the IEEE 802.3af and IEEE 802.3at standards.

In addition, this cable features our specially developed plug design, which is characterized by easy operation of the jack and a narrow and short design.

SLIM-L-UU-K6A ORANGE

CAT6A 10 Gigabit LightPatch Cord round, U/UTP, Ø 3,6 mm, orange

Product Features	
Fire retardant version	Yes
AWG-size	AWG28
Pining	TIA/EIA 568 B
Color	Orange
Color anti-kink sleeve	Orange
Halogen free according to EN IEC 60754-1	Yes
Halogen free according to EN IEC 60754-2	Yes
Halogen free according to EN IEC 60754-3	Yes
Cable construction	4x2
Cable Structure	Ø 3,6 mm
Cable Type	U/UTP
Category	CAT.6A (IEC)
Anti-kink sleeve	Moulded-on
Copper Cable Construction	4x2xAWG28/7
Length	0.1 m / 0.15 m / 0.25 m / 0.5 m / 1 m / 1.5 m / 10 m / 2 m / 3 m / 5 m / 7.5 m
Coating	LSOH
Color outer sheath	Orange
max. Data Transfer	10 Gigabit
Oil resistant according to EN IEC 60811-404	No
Pin assignment	1:1
PoE	Yes
Locking lever	Yes
Shield	U/UTP unshielded
Type of Connector Connection 1	RJ45 8(8)
Type of Connector Connection 2	RJ45 8(8)



Product Number		EAN Code
SLIM-L-UU-K6A 0.1 OR	0.1 Meter	9120138893433
SLIM-L-UU-K6A 0.15 OR	0.15 Meter	9120138893525
SLIM-L-UU-K6A 0.25 OR	0.25 Meter	9120138893617
SLIM-L-UU-K6A 0.5 OR	0.5 Meter	9120138893709
SLIM-L-UU-K6A 1.0 OR	1.0 Meter	9120138893792
SLIM-L-UU-K6A 1.5 OR	1.5 Meter	9120138893884

SLIM-L-UU-K6A ORANGE

CAT6A 10 Gigabit LightPatch Cord round, U/UTP, Ø 3,6 mm, orange

SLIM-L-UU-K6A 10.0 OR	10.0 Meter	9120138893976
SLIM-L-UU-K6A 2.0 OR	2.0 Meter	9120138894065
SLIM-L-UU-K6A 3.0 OR	3.0 Meter	9120138894157
SLIM-L-UU-K6A 5.0 OR	5.0 Meter	9120138894249
SLIM-L-UU-K6A 7.5 OR	7.5 Meter	9120138894331